RADICI

Living

Collection

Ferrara

Athens

Napoli / Napoli Linea

Parma

1870

24115

2474

1893

18289

18410

1875

1876

2477

Bologna

222570

222594

222593


222520

222541

222582

222583

222575


222574


222576

222578

222573


222577

Bologna Linea

2228377

2227883


2227877


2227873

Assisi

244647

244555

244556

244575

244547

244573

244677

244578

Parma

CONSTRUCTION
Tufted Cut Pile- Frisée 1/10”

COMPOSITION
100% Polyamide ECONYL SD

SECONDARY BACKING
POLYFLEX

STITCHES PER M²
± 178000

PILE HEIGHT ± 5.5 mm

TOTAL HEIGHT± 6.2 mm

YARN WEIGHT ± 1100 g/m²

TOTAL WEIGHT ± 4800 g/m²

TILE SIZE 50x50 cm

COLOUR FASTNESS TO LIGHT 4-5
INSULATION IMPACT NOISE ΔLw 25 db
THERMAL RESISTANCE m² K/W ≤ 0,17
BODY VOLTAGE WALKING TEST K/W ≤ 2

Bologna + Linea

CONSTRUCTION
Tufted Loop Pile 1/10”

COMPOSITION
100% Polyamide SD

SECONDARY BACKING
POLYFLEX

STITCHES PER M²
± 189600

PILE HEIGHT ± 3.0 mm

TOTAL HEIGHT ± 5.4 mm

YARN WEIGHT± 540 g/m²

TOTAL WEIGHT ± 4100 g/m²

TILE SIZE 50x50 cm

COLOUR FASTNESS TO LIGHT 5
INSULATION IMPACT NOISE ΔLw 24 db
THERMAL RESISTANCE m² K/W ≤ 0,17
BODY VOLTAGE WALKING TEST K/W ≤ 2

Ferrara

CONSTRUCTION
Tufted Loop Pile 1/10”

COMPOSITION
100% Polyamide SD

SECONDARY BACKING
POLYFLEX

STITCHES PER M²
± 164000

PILE HEIGHT ± 2.6 mm

TOTAL HEIGHT ± 5.4 mm

YARN WEIGHT ± 550 g/m²

TOTAL WEIGHT ± 3990 g/m²

TILE SIZE 50x50 cm

COLOUR FASTNESS TO LIGHT 5
INSULATION IMPACT NOISE ΔLw 23 db
THERMAL RESISTANCE m² K/W ≤ 0,17
BODY VOLTAGE WALKING TEST K/W ≤ 2

Napoli + Linea

CONSTRUCTION
Tufted Loop Pile 1/10”

COMPOSITION
100% Polyamide SD

SECONDARY BACKING
POLYFLEX

STITCHES PER M²
± 187000

PILE HEIGHT ± 3.5 mm

TOTAL HEIGHT ± 5.4 mm

YARN WEIGHT± 550 g/m²

TOTAL WEIGHT ± 4100 g/m²

TILE SIZE 50x50 cm

COLOUR FASTNESS TO LIGHT 5
INSULATION IMPACT NOISE ΔLw 24 db
THERMAL RESISTANCE m² K/W ≤ 0,17
BODY VOLTAGE WALKING TEST K/W ≤ 2

Assisi

CONSTRUCTION
Tufted Loop Pile –Scroll 1/10”

COMPOSITION
100% Polyamide SD

SECONDARY BACKING
POLYFLEX

STITCHES PER M²
± 177750

PILE HEIGHT ± 2.2 mm

TOTAL HEIGHT ± 5.5 mm

YARN WEIGHT ± 550 g/m²

TOTAL WEIGHT ± 3900 g/m²

TILE SIZE 50x50 cm

COLOUR FASTNESS TO LIGHT 5
INSULATION IMPACT NOISE ΔLw 20 db
THERMAL RESISTANCE m² K/W ≤ 0,17
BODY VOLTAGE WALKING TEST K/W ≤ 2

Special Sizes Available
(Felt backing option available):

For a minimum of 500 SQM:

48×48 cm
60×60 cm
60.96×60.96 cm

For a minimum of 100 SQM:

100×100 cm

For a minimum of 200 SQM:

100×50 cm
100×25 cm
25×100 cm
100×200 cm
100×150 cm

Please consider a 2% production coverage.

Athens

CONSTRUCTION
Tufted Loop Pile 1/10”

COMPOSITION
100% Polyamide SD

SECONDARY BACKING
POLYFLEX

STITCHES PER M²
± 173360

PILE HEIGHT ± 3.5 mm

TOTAL HEIGHT ± 5.2 mm

YARN WEIGHT ± 510 g/m²

TOTAL WEIGHT ± 3800 g/m²

TILE SIZE 50x50 cm

COLOUR FASTNESS TO LIGHT 5
INSULATION IMPACT NOISE ΔLw 24 db
THERMAL RESISTANCE m² K/W ≤ 0,17
BODY VOLTAGE WALKING TEST K/W ≤ 2

Special Sizes Available
(Felt backing option available):

For a minimum of 500 SQM:

48×48 cm
60×60 cm
60.96×60.96 cm

For a minimum of 100 SQM:

100×100 cm

For a minimum of 200 SQM:

100×50 cm
100×25 cm
25×100 cm
100×200 cm
100×150 cm

Please consider a 2% production coverage.